



Features

- Peak measurement with 0,2 % accuracy and high measurement rate allows to detect tensile and break forces precisely
- Up to 150 hours battery operation time with rechargeable LiPo battery
- Autoreverse display enables use as handheld device or test stand mounting
- Overload protection up to 500 % » with rugged aluminium die cast housing

Technical data

		Order No.:						
		FMI-B20B5	FMI-B20C1	FMI-B20C2	FMI-B20C5	FMI-B20K1	FMI-B20K2	FMI-B20K5
Capacity F(nom) *	N	50	100	250	500	1000	2500	5000
Resolution **	N	0,01	0,02	0,05	0,1	0,2	0,5	1
Tolerance **	% F(nom)	0,2						
Temperature coefficient*	% / K	0,02						
Reproducibility*	% F	0,04						
Repeatability*	% F	0,04						
Hysteresis*	% F	0,1						
Measuring principle		Bidirectional force sensor with strain gauges and high-speed ?-processor						
Nominal deflection*	mm	0,13	0,25	0,23	0,17	0,34	0,13	0,26
Measuring shaft		M6					M10	
Max. operating force*	% F(nom)	120						
Breaking force*	% F(nom)	500					200	

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en



FMI-B20

Digital Force Gauge - HR

Display	Type	5-digit LCD 12mm Autoreverse	
	Update (msec)	100 ... 1000	
Operation modes	Regular	N kg lb	
	Peak (real-time)	Display of peak value Peak value of pull- or push force (drag indicator function)	
	Limits + Statistik	-	
Interface	USB	without	
	Hirose	without	
	Sensor	without	
Power supply	Type	internal LiPo battery operation time 150h	
	Charging	USB (Buchse)	
Temperature (operation)*	°C	0 ... 40	
Protection code (EN 60529)	Cable not plugged	IP40	IP65
Housing	Material	Aluminium die cast	Hardened steel
	LxWxH (mm)	150 x 82 x 29	
	Gewicht (g)	480	1.150
	Mounting	2xM4, 2xM5, adjusting holes D5(H7)	

Scope of Supply

Force gauge with hook, flat head, notched head, conical head, VAC universal charger with EC-, UK- and US-wall plug connector, quickstart operation manual, protection case.

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en