



Features

- Data logging and USB interface » with memory function and limit value monitoring
- Peak measurement with 0,15 % accuracy » a high measurement rate allows to detect tensile and break forces precisely
- Application as force sensor in test stands » with rugged aluminium die cast housing, optimized fixing points and autoreverse display

Technical data

Order No.:

		Order No.:								
		FMI-B30A5	FMI-B30B1	FMI-B30B5	FMI-B30C1	FMI-B30C2	FMI-B30C5	FMI-B30K1	FMI-B30K2	FMI-B30K5
Capacity F(nom)*	N	5	10	50	100	250	500	1000	2500	5000
Resolution	N	0,001	0,002	0,01	0,02	0,05	0,1	0,2	0,5	1
Accuracy	%	0,15								
Temperature coefficient*	%/K	0,02								
Reproducibility*	% F(nom)	0,03								
Repeatability*	% F	0,03								
Hysteresis*	% F	0,075								
Creeping (5min)*	% F	0,1								
Measuring principle		Bidirectional force sensor with strain gauges and high-speed ?-processor								
Nominal deflection*	mm	0,17	0,34	0,13	0,25	0,23	0,17	0,34	0,13	0,26
Measuring shaft		M6							M10	
Max. operating force*	% F(nom)	120								

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en



Breaking force*	% F(nom)	500	200
Display	Type	5-digit LCD 12mm Autoreverse	
	Refresh time (ms)	100 ... 1000	
Operation modes	Regular	N kg lb	
	Peak (real-time)	Display of peak value Peak value of pull- or push force (drag indicator function)	
	Limits + Statistics	2 separately adjustable limits Single value memory and continuous measured value memory	
Interface	USB	USB 2.0 data communication	
	Hirose	Limit / overload signals, digital I/O's (1 input / 3 outputs), trigger, supply (optional data cable required)	
	Sensor	without	
Power supply	Type	internal LiPo battery operation time 150h	
Temperature (operation)*	°C	0 ... 40	
Protection code (EN 60529)	Cable not plugged	IP40	IP65
Housing	Material	Aluminium die cast	Hardened steel
	LxWxH (mm)	150 x 82 x 29	
	Weight (kg)	0,480	1,150
	Mounting	2xM4, 2xM5, adjusting holes D5(H7)	

Scope of Supply

Force gauge with force introduction parts (hook, flat head, groove head, pressure cone), 100-240VAC Universal mains charger with EU, UK and US plug adapter, USB cable, Quickstart manual, transport and protective case. Free software for MsExcel data transfer to download.

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en