




Features



- Controller panel with bright full color 10,4" touch screen display.
- Manual operation and preconfigured, automated test procedures. Test plans can be added via the customer portal.
- Online display of force vs. length diagrams, result data download with webBrowser
- Compatible with universal testing machines series FMT-310/311 (build 2006 and later)

Technical data

		Order No.:
		FMT-317CU
Active area	mm	211x158
Touch	Type	PCAP
Version		1.00
Resolution - Force	rel.	1 / 10.000
Resolution - Length	mm	0,001
Resolution - Speed	mm/min	1
Resolution - Stroke	mm/min	0,01
Power supply		from drive unit
Consumption	A @ 230 V AC	1,8
Machine interface	Type	D-Sub, 37-P
2 USB (socket)	Type	USB 2.0
Ethernet (socket)	Type	100Base-TX (RJ45)

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en



2 Digital IN (Optocoupler)	Type	5V Pull-Up
3 Digital OUT	Type	24 V Push-Pull
2 Analog IN (A/D-Converter)	Type	0-20 mA (12-Bit) / 0-10V (12-Bit)
Service interface	Type	D-Sub, 9-P
Temperature - operation	°C	10 - 35
Temperature - trans/store	°C	-10 - 60
Dimensions (LxWxH)	mm	241 x 191 x 46 (220)
Mounting	Type	100 mm - Vesa
Weight	kg	2,6

Scope of Supply

Control panel with 37-p interface cable (app. 1,5 m) for universal testing machine, adjustable stand, RJ45 Cat 6A patch cable (app. 1,5m), 15-p D-sub-socket and operation manual. Latest operation system version and software version installed and default equipment configuration.

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en